

## **25W Single Output SM Series**



## Features:

- AC input / full range
  - Miniature size, high power density
  - Top international brand components for key parts
  - UL, CE approved (refer to spec. of each series)
  - Protections: overload/ over voltage/ short circuit
  - 5 years limited warranty


Model No.	HF25W-SSM
Dimension (mm)	F6025MW: 78×51×28
Weight & packing (/CTN)	0.18kg, 90pcs
AC input voltage range	88~264VAC (124~370VDC)
Input frequency	47~63Hz
Inrush current	cold start, 20A/115V, 40A/230V
Input leakage current	< 1mA/ 230VAC
Line regulation (full load)	≤± 0.5%
Voltage adjust range	± 10%
Overload protection	105~150%, hiccup mode, auto recovery
Over voltage protection	clamping by zener diode
Withstand voltage	I/P -O/P: 3.0KVAC/1min; I/P -F/G: 1.5KVAC/1min; O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temperature	-20°C~+70°C (refer to the derating curve)
Safety standards	GB4943, UL60950, EN60950
EMC standards	GB9254, EN55022 class B, EN55024, EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

## 25W Single Output

ce

Model	DC Output		Load regul.	R&N	Efficiency
HF25W-SSM-5	5V	5.0A	0.5%	80mV	78%
HF25W-SSM-12	12V	2.1A	0.5%	120mV	82%
HF25W-SSM-15	15V	1.7A	0.5%	120mV	82%
HF25W-SSM-24	24V	1.1A	0.5%	150mV	85%
HF25W-SSM-48	48V	0.57A	0.5%	150mV	85%

# Drawing



F6025MW